

OpenCode install on Linux Mint

Software installation

Install with the bash script from the opencode website:

```
curl -fsSL https://opencode.ai/install | bash
```

reload your shell (or login again) `exec zsh`

verify with:

```
opencode --version
```

Auto-Start at Boot time

Create a systemd Service File

`sudo vi /etc/systemd/system/opencode.service`
add:

```
[Unit]
Description=OpenCode AI Assistant
After=network.target

[Service]
Type=simple
User=abel
WorkingDirectory=%h/opencode/projects
ExecStart=/usr/local/bin/opencode web --port 4096 --hostname 0.0.0.0
Restart=always
RestartSec=10

[Install]
WantedBy=multi-user.target
```

User=abel seems unsafe but that is how it works, and seeing as it is on the personal workstation any security risk is minimal.

start and enable

Start and enable opencode by:

```
sudo systemctl enable opencode --now
```

Last update:

2026/03/25 11:22 installatie_handleidingen:openclode https://wiki.auriel.nl/doku.php?id=installatie_handleidingen:openclode&rev=1774434136

From:

<https://wiki.auriel.nl/> -

Permanent link:

https://wiki.auriel.nl/doku.php?id=installatie_handleidingen:openclode&rev=1774434136 

Last update: **2026/03/25 11:22**