

Re-sign an rpm with another GPG key

bekijk de op het systeem geïmporteerde GPG keys:

```
rpm -q gpg-pubkey -qf '%{NAME}-%{VERSION}-%{RELEASE}\t%{SUMMARY}\n'
```

```
gpg-pubkey-fd431d51-4ae0493b      gpg(Red Hat, Inc. (release key 2)
<security@redhat.com>)
gpg-pubkey-2fa658e0-45700c69      gpg(Red Hat, Inc. (auxiliary key)
<security@redhat.com>)
gpg-pubkey-4bd6ec30-4ff1e4fa      gpg(Puppet Labs Release Key (Puppet Labs
Release Key) <info@puppetlabs.com>)
gpg-pubkey-0608b895-4bd22942      gpg(EPEL (6) <epel@fedoraproject.org>)
gpg-pubkey-c3fac2bd-56ba04ba      gpg(RWSBUILD)
gpg-pubkey-5dbe67ee-56bc7bf3      gpg(RWSBUILD)
gpg-pubkey-66fd4949-4803fe57      gpg(VMware, Inc. -- Linux Packaging Key --
<linux-packages@vmware.com>)
gpg-pubkey-ef8d349f-57b6233e      gpg(Puppet, Inc. Release Key (Puppet, Inc.
Release Key) <release@puppet.com>)
gpg-pubkey-001e5cc9-5849fa8b      gpg(VMware, Inc. (Linux Packaging Key)
<linux-packages@vmware.com>)
gpg-pubkey-a14fe591-578876fd      gpg(Zabbix LLC <packager@zabbix.com>)
```

```
vi ~/.rpmmacros
```

zet daar in:

```
%__os_install_post %{nil}
%_topdir
%(echo $HOME)/rpmbuild
%_tmppath
%(echo $HOME)/rpmbuild/rpm

%_signature gpg
%_gpg_name   RWSBUILD
```

```
rpm -qpi XXXX.rpm
```

“gpg -with-fingerprint GPG-KEY-FILE” laatste 4 octets van Key fingerprint is de Key ID

From:
<https://wiki.auriel.nl/> -

Permanent link:
https://wiki.auriel.nl/doku.php?id=werkinstructies:re-sign_a_rpm

Last update: **2021/08/27 10:45**

