

Scanbd met een USB Scanner op Raspbian

work in progress

scanner koppelen

koppel de scanner aan de server.

Check of de scanner aanwezig is: `lsusb`

```
root@raspberrypi:~# lsusb
Bus 001 Device 004: ID 03f0:1705 Hewlett-Packard ScanJet 5590
Bus 001 Device 003: ID 0424:ec00 Standard Microsystems Corp. SMSC9512/9514
Fast Ethernet Adapter
Bus 001 Device 002: ID 0424:9512 Standard Microsystems Corp. LAN9500
Ethernet 10/100 Adapter / SMSC9512/9514 Hub
Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub
root@raspberrypi:~#
```

In dit geval zien we daar de HP ScanJet 5590.

software installeren

de scan software sane met drivers

```
apt-get install sane-utils
apt-get install libsane-hpaio
```

edit de backend file: `vi /etc/sane.d/dll.conf`

en laat alleen net en hp en hp5590 staan.

```
neem de device ID uit het resultaat van lsusb echo "usb 0x03F0 0x1705"
>/etc/sane.d/hp5590.conf
sane-find-scanner
```

als het klopt zie je:

```
found USB scanner (vendor=0x03f0 [Hewlett-Packard], product=0x1705 [hp
scanjet scanner]) at libusb:001:004
```

Test of de scan software met de scanner praat:

```
scanimage -p -x 208 -y 297 -format tiff -mode Color -resolution 300 >
/tmp/testscan2.tif
```

Haal het bestand over en check of de afbeelding klopt.

graphische manipulaite software

```
apt-get install ImageMagick  
apt-get install netpbm
```

Scandb

```
apt-get install scanbd
```

https://wiki.archlinux.org/index.php/Scanner_Button_Daemon

Knoppen acties definieren

gcc compiler

installeer de nodige developement libs:

```
yum install libconfuse-devel gbus-devel sane-backends-devel
```

```
Installed:  
sane-backends-devel.x86_64 0:1.0.24-9.el7  
Dependency Installed:  
libieee1284-devel.x86_64 0:0.2.11-15.el7          libjpeg-turbo-  
devel.x86_64 0:1.2.90-5.el7  
libtiff-devel.x86_64 0:4.0.3-14.el7          libusb-devel.x86_64  
0:1.0.15-4.el7  
  
Complete!
```

Installeer de gcc compiler

```
yum install gcc
```

noteer wat wordt geïnstalleerd voor straks bij het opruimen:

```
Installed:  
gcc.x86_64 0:4.8.3-9.el7  
  
Dependency Installed:  
cpp.x86_64 0:4.8.3-9.el7          glibc-devel.x86_64 0:2.17-78.el7          glibc-  
headers.x86_64 0:2.17-78.el7  
kernel-headers.x86_64 0:3.10.0-229.14.1.el7  libmpc.x86_64 0:1.0.1-3.el7
```

```
mpfr.x86_64 0:3.1.1-4.el7
```

```
Complete!
```

build de software

haal de sourcecode op en pak die uit:

```
cd /tmp
wget
http://downloads.sourceforge.net/project/scanbd/releases/scanbd-1.4.3.tgz tar
-xvzf scanbd-1.4.3.tgz
cd 1.4.3
```

vervolgens configureren, compileren en installeren:

```
./configure
make
make install
```

software afconfigureren

cleanup

Bronnen

https://wiki.debian.org/SaneOverNetwork#Server_Configuration

<https://help.ubuntu.com/community/sane>

From:
<https://wiki.auriel.nl/> -

Permanent link:
https://wiki.auriel.nl/doku.php?id=werkinstructies:scanbd_met_usb_scanner&rev=1510852413



Last update: **2017/11/16 18:13**