

# Simpele PXE/tftp boot files om mee te testen

```
yum install syslinux
```

```
cp -r /usr/share/syslinux/* /var/lib/tftpboot
```

```
mkdir /var/lib/tftpboot/pxelinux.cfg
```

```
touch /var/lib/tftpboot/pxelinux.cfg/default
```

```
vi /var/lib/tftpboot/pxelinux.cfg/default
```

en zet hier in:

```
default menu.c32
```

```
prompt 0
```

```
timeout 300
```

```
ONTIMEOUT local
```

```
menu title ##### PXE Boot Menu #####
```

```
label 1
```

```
menu label ^2) Install CentOS 7 x64 with http://mirror.centos.org Repo
```

```
kernel centos7/vmlinuz
```

```
append initrd=centos7/initrd.img
```

```
method=http://mirror.centos.org/centos/7/os/x86_64/ devfs=nomount ip=dhcp
```

```
label 2
```

```
menu label ^4) Boot from local drive
```

From:

<https://wiki.auriel.nl/> -

Permanent link:

[https://wiki.auriel.nl/doku.php?id=werkinstructies:simpele\\_pxe\\_tftp\\_boot\\_server&rev=1612109816](https://wiki.auriel.nl/doku.php?id=werkinstructies:simpele_pxe_tftp_boot_server&rev=1612109816)



Last update: **2021/01/31 17:16**