

Simpele PXE/tftp boot files om mee te testen

installeer de TFTP server

```
yum install tftp-server
```

Set up de boot files

```
yum install syslinux
```

```
cp -r /usr/share/syslinux/* /var/lib/tftpboot  
mkdir /var/lib/tftpboot/pxelinux.cfg  
touch /var/lib/tftpboot/pxelinux.cfg/default
```

```
vi /var/lib/tftpboot/pxelinux.cfg/default
```

en zet hier in:

```
default menu.c32  
prompt 0  
timeout 300  
ONTIMEOUT local  
  
menu title ##### PXE Boot Menu #####  
  
label 1  
menu label ^2) Install CentOS 7 x64 with http://mirror.centos.org Repo  
kernel centos7/vmlinuz  
append initrd=centos7/initrd.img  
method=http://mirror.centos.org/centos/7/os/x86_64/ devfs=nomount ip=dhcp  
  
label 2  
menu label ^4) Boot from local drive
```

start de TFTP server

Bronnen

<https://www.tecmint.com/install-pxe-network-boot-server-in-centos-7/>

https://www.golinuxcloud.com/configure-kickstart-pxe-boot-server-linux/#Step_3_Setup_PXE_boot_server

From:
<https://wiki.auriel.nl/> -

Permanent link:
https://wiki.auriel.nl/doku.php?id=werkinstructies:simpele_pxe_tftp_boot_server&rev=1612127571 

Last update: **2021/01/31 22:12**